



DROP FORGED LINK CHAINS



Type A



Type D

Alternative to type D

| Chain type | Type | Pitch | Link width | Bar thickness | | Link height | Attachment slot | Hole | Breaking load | | | | Weight (kg/m) | | | | | |
|------------|------|-------|------------|---------------|------|-------------|-----------------|------|----------------|----------------|------|----------------|------------------|------------------|-----------|-------------|--------|------------|
| | | | | p | s | | | | s ₁ | s ₂ | g | g ₁ | | Ø d ₁ | 20MnCr5e* | 18NiCrMo5e* | C40V** | 42CrMo4V** |
| | | | | (mm) | (mm) | | | | (mm) | (mm) | (mm) | (mm) | | (mm) | (kN) | (kN) | (kN) | (kN) |
| R100101 | A | 101,6 | 24 | 6 | 8,0 | 36 | - | 14 | 90 | 95 | 100 | 130 | 3,85 | | | | | |
| R100102 | A | 101,6 | 30 | 8 | 12,0 | 36 | - | 14 | 120 | 130 | 150 | 200 | 5,25 | | | | | |
| R200101 | A | 102,0 | 25 | 6 | 8,0 | 36 | - | 14 | 75 | 85 | 90 | 120 | 3,95 | | | | | |
| R100103 | A | 142,0 | 24 | 6 | 8,0 | 47 | - | 20 | 110 | 120 | 145 | 200 | 4,50 | | | | | |
| R100104 | A | 142,0 | 42 | 11 | 19,0 | 50 | - | 25 | 270 | 280 | 350 | 440 | 10,40 | | | | | |
| R100105 | A | 142,0 | 62 | 15 | 28,0 | 50 | - | 25 | 370 | 400 | 500 | 600 | 14,90 | | | | | |
| R200102 | A | 142,0 | 56 | 18 | 25,0 | 50 | - | 25 | 310 | 350 | 400 | 480 | 12,50 | | | | | |
| R100106 | A | 150,0 | 24 | 6 | 8,0 | 50 | - | 20 | 110 | 120 | 145 | 200 | 5,00 | | | | | |
| R100107 | A | 150,0 | 42 | 12 | 15,5 | 47 | - | 25 | 230 | 250 | 300 | 340 | 10,00 | | | | | |
| R100108 | A | 160,0 | 50 | 12 | 23,0 | 50 | - | 25 | 300 | 320 | 400 | 520 | 10,50 | | | | | |
| R200103 | A | 160,0 | 42 | 12 | 20,0 | 45 | - | 20 | 260 | 275 | 320 | 380 | 11,00 | | | | | |
| R300175 | D | 175,0 | 72 | 22 | 30,0 | 60 | 11,0 | 30 | 500 | 550 | 600 | 710 | 15,00 | | | | | |
| R100109 | A | 200,0 | 66 | 17 | 32,0 | 60 | - | 28 | 530 | 580 | 650 | 750 | 16,30 | | | | | |
| R200105 | A | 200,0 | 54 | 15 | 25,5 | 50 | - | 25 | 310 | 350 | 400 | 480 | 12,80 | | | | | |
| R200106 | D | 200,0 | 52 | 18 | 25,0 | 50 | 13,0 | 25 | 300 | 340 | 330 | 460 | 11,50 | | | | | |
| R200107 | D | 200,0 | 58 | 17 | 25,0 | 50 | 11,5 | 25 | 310 | 350 | 450 | 550 | 13,00 | | | | | |
| R200108 | D | 200,0 | 70 | 20 | 30,0 | 60 | 13,0 | 30 | 500 | 550 | 600 | 750 | 19,40 | | | | | |
| R300216 | A | 216,0 | 64 | 20 | 26,0 | 73 | - | 35 | 480 | 500 | 630 | 700 | 20,00 | | | | | |
| R100110 | A | 250,0 | 70 | 20 | 31,0 | 75 | - | 34 | 600 | 650 | 750 | 1.000 | 24,00 | | | | | |
| R200110 | A | 250,0 | 66 | 18 | 33,0 | 60 | - | 28 | 530 | 580 | 650 | 750 | 14,00 | | | | | |
| R200111 | D | 250,0 | 70 | 20 | 30,0 | 60 | 13,0 | 30 | 500 | 550 | 600 | 700 | 16,00 | | | | | |
| R100111 | A | 260,0 | 70 | 21 | 31,0 | 75 | - | 34 | 600 | 650 | 750 | 1.000 | 21,65 | | | | | |

* case-hardened ** hardened and tempered

■ Calculated theoretical breaking load □ Tested breaking load ■ Chain available, but new tool required